

Product Description:

Nexkemia welcomes the **MT Series E30** (Modified Graphite grade) containing 30 % recycled material to its NexEco line up of EPS products. **NexTherm** is NexKemia's new option for improved insulating performance over traditional expandable polystyrene (EPS). The pentane (blowing agent) concentration and bead size range provide optimal achievable EPS density targets from 1.0 to 3.0 pcf. The MT series E30 is suitable for a wide range of applications requiring improved insulating properties. The MT series E30 eps resin is best described as black beads, are slightly lentil in shape, and are produced by a state-of-the-art extrusion process.

Applications:

MT Series E30 EPS can be used in many applications including but not limited to:

Block Molding	Shape Molding
<ul style="list-style-type: none">• Protective Packaging• Suitable for use with EPS/Regrind materials• Many Additional Applications	<ul style="list-style-type: none">• Thick wall (> 1 cm) applications• Many Additional Applications

Compliance & Documentation:

NexKemia MT Series E30 is manufactured to comply with:

- GreenGuard Gold

Technical Data:

NexKemia MT Series Modified EPS	Typical Pentane Value (%wt.)	Unexpanded Beads Size Distribution (mm)	Recommended Expanded Density Range (pcf)
MT55L-E30	5.5	0.85-1.40 mm (95%)	0.95 – 1.80
MT55K-E30	5.5	0.85-1.40 mm (95%)	0.95 – 1.80
MT35L-E30	5.5	0.40-0.85mm (95%)	1.15 – 3.00
MT35K-E30	5.5	0.40-0.85mm (95%)	1.15 – 3.00

Processing:

Pre-Expansion	Maturation Time	Molding
<p>Single pass expansion: to optimize pre-expansion and achieve a homogeneous density from bead to bead, a slower expansion rate is recommended. By optimizing the expansion cycle, the uniformity of the pre-expanded beads will help to provide more consistent and uniform molding.</p> <p>Second pass: to achieve lower densities (<0.95 pcf) it is recommended that the products be pre-expanded in two stages</p>	<p>Aging times may range between 24 to 72 hours. The maturation time will vary according to the density targeted. Please contact your sales or technical support representative for more details.</p>	<p>NexKemia EPS is designed to be molded with commercially available EPS processing machinery (horizontal and vertical block molds and shape presses).</p>

For additional product information please contact your NexKemia representative.

General Information

Product Packaging

- All **Nexkemia EPS** materials are packaged in 1,000 Kgs. (2,205 Lbs.) Super-sacks. A typical full truckload shipment consists of 20 Super-sacks of eps material with a total delivered weight of 20,000 Kgs. (44,100 Lbs.) per truckload.

Safety and Handling

- Electrostatic discharges may be generated during the use and manipulation of any EPS product.
- All metallic equipment and machinery should be grounded in accordance with all local government safety ordinances.
- Only use spark-proof tools in all areas where EPS is stored and processed.
- NexKemia **MT Series E30** products contain a flame-retardant additive and are not suitable for food contact applications
- For more information, refer to the NexKemia Safety Data Sheet (SDS) prior to use.
- Upon delivery, trailer and/or container should be opened and allowed to vent for a minimum of one hour before unloading.

Storage

All EPS materials should be:

- Stored in unopened containers in dry and well-ventilated areas. The recommended storage temperature range for EPS is 15-25°C (68-77°F).
- Protected against unsuitable weather conditions and direct sun light.
- Kept away from heat, sparks, flame, and other sources of ignition.

Shelf Life

- In order to attain and maintain the ideal product performance of NexKemia EPS, it is recommended to process all product materials within 6 months of the date of fabrication.
- Any opened containers should be closed properly to minimize excess air in the product bag and should be processed within a short period time.

End Products


- Finished gray foam products should be kept away from prolonged direct sunlight. End products should be wrapped in opaque white films.

Disclaimer: NexKemia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof. As NexKemia cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. IN NO EVENT SHALL NEXKEMIA BE LIABLE FOR ANY DIRECT, INCIDENTAL, CONSEQUENTIAL, INDIRECT, STATUTORY, SPECIAL, EXEMPLARY OR PUNITIVE DAMAGES, INCLUDING, BUT NOT LIMITED TO, LOST PROFITS, LOSS OF USE, LOSS OF TIME, SHUTDOWN OR SLOWDOWN COSTS, INCONVENIENCE, LOSS BUSINESS OPPORTUNITIES, DAMAGE TO GOODWILL OR REPUTATION, OR OTHER ECONOMIC LOSS, REGARDLESS OF WHETHER SUCH LIABILITY IS BASED ON BREACH OF CONTRACT, TORT, STRICT LIABILITY OR OTHERWISE, AND EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES OR SUCH DAMAGES COULD HAVE BEEN REASONABLY FORESEEN. NEXKEMIA DOES NOT PROVIDE ANY WARRANTY FOR THE PRODUCT, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES THAT THEY ARE OF MERCHANTABLE QUALITY OR THAT THEY CAN BE USED FOR ANY PARTICULAR PURPOSE.

Revised: May 2024



EXPANDING A WORLD OF INNOVATION



**24 Bellevue Street
Mansonville, QC
J0E 1X0 Canada
1.450.292.3333
info@nexkemia.com**

